

AB-U950/U951



PRODUCT NAME: Single barcode Label Printer
MODEL#: AB-U950/U951

Excellent Quality, Stable and Durable

HIGHLIGHTS

Support kinds of waybill printing, it is also printing dispatch bill and bar code sticker.
Printing paper: continuous thermal paper, black-label paper, perforated paper and so on.
Paper width: 108mm, big paper roll diameter: 175mm
Excellent printing speed up to 150mm/s
Automatic test paper

Wide usage: Express, Logistic, E-commerce
ISO9001: 2000 qualified enterprise.

Product type: Nakazaki AB-U951 barcode label printer
Printing method: direct thermal
Resolution: 203DPI
Print width: 108mm
Printing speed: 150mm/s
Interface: USB, serial port
Hardware ID: USBPRINTAB-U95105E4

SPECIFICATION

| | | |
|----------------------------|--|------------------------|
| Model | AB-U950 | AB-U951 |
| Printing | Thermal dot line printing | |
| dot density | 8 dots / mm | |
| heating element dot | 864 dots/mm | |
| Print speed | 150mm/s (MAX) | |
| Print width | 104mm (MAX) | |
| Print length | 1000mm (MAX) | |
| Print paper | Big roll OD: 175mm (MAX), Small roll OD: 100mm (MAX) | |
| Cutter type | Manual tearing | |
| Paper type | continuous thermal paper, black-label paper, perforated paper | |
| Paper width | 32~114mm | |
| paper height | 40~1000mm | |
| Paper thickness | MAX: 0.254mm(10mil) , min: 0.06mm(2.36mil) | |
| Paper roll Dimension | 25.4mm~76mm(1''~3'') | |
| Paper clearance height | Min: 2mm(0.09'') | |
| Receive buffer | 8MB | |
| Interface | Serial RS232, USB | |
| power | DC24V, 2A | DC24V, 3.5A |
| Standby | 1.5W | |
| Rated power | 40W | |
| Max power | 140W | |
| Wear life | Printing head: 150km | |
| Environment | Working temperature and humidity: -5~50°C;10~90%RH Storage temperature and humidity: -40~80°C;5~90%RH | |
| Dimension | 222(L)x131(W)x135(H)mm | 275(L)x175(W)x150(H)mm |
| Packing dimension | 316(L)x225(W)x170(H)mm | 351(L)x222(W)x196(H)mm |
| Net weight | 1.58KG | 1.65KG |
| Gross weight | 2.67KG | 2.92KG |
| Transport packing quantity | 8 | |