



# SMART POS SERIES

## ZQ-P1088 max

### HIGHLIGHTS

- Main housing made by Aluminum
- Built-in 80mm Seiko mechanism thermal printer
- Various options of peripherals
- Capacitive multi-points touch panel
- Fanless design
- Operator display angles adjustable

### Optional

- MSR/ Dallas key/RFID

## SPECIFICATIONS

Model		ZQ-P1088 Max	
CPU	Intel® Atom™ Processor D2550	Audio	Interface x 1
Memory	1 x DDR3 2GB	VGA	1 x DB-15 VGA Interface
Network	RTL8168DE PCI-E Gigabit Ethernet NIC	HDMI	N/A
Power Supply	100-240V/ 3.5A 47~63Hz	DISPLAY	
Video Card	Intel Graphics Media	Viewing Angle	85 degree adjustable
Sound Card	Accelerator3150(256MB/Intel)	LCD	15" TFT LCD
	RTL ALC662 @INTEL 82801G(ICH7)High Definition Audio	Max. Resolution	1024 x 768
Dimension	350x225x375mm	Touch Screen	5-wires resistive 20,000,000 times touch life (P-CAP multi-touch optional)
O.S. Compliant	Windows XP / VISTA/WIN7/WIN8(optional)	ENVIRONMENT	
SSD	M-SATA 32 G	Operation Temperature	0~40
I/O PORTS		Storage Temperature	- 40~50
USB	4 x USB 2.0 port	Humidity	38~80%
Serial Port	3 x DB-9 RS232		
LAN	1 x 10/100/1000 Mbps		



Capacitive Touch Panel and LCD Adjustable



Customer Display



Optional MSR



Optional I-button



Various interfaces